

---

Subject: 250 Bass Amp Head

Posted by [chemita57](#) on Fri, 05 Mar 2021 05:42:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Do the small rivets on the sides of the rear panel of the amp head need to be drilled out to pull out the electronics?

---

---

Subject: Re: 250 Bass Amp Head

Posted by [stevem](#) on Fri, 05 Mar 2021 10:33:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The complete chassis slides out the rear of the cabinet by removing the four 10/32 machine screws on the bottom of the cabinet, do not remove the 4 metal feet on the bottom if they are still there.

Do not drill out the rivets as they hold the chassis together . Why is it you need to gain access to the inside of the amp

---

---

Subject: Re: 250 Bass Amp Head

Posted by [chemita57](#) on Fri, 05 Mar 2021 15:23:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I need to clean out the pots and replace the bulbs. By the way, what size bulbs does this require.

---

---

Subject: Re: 250 Bass Amp Head

Posted by [chemita57](#) on Sat, 06 Mar 2021 14:34:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Thanks for the info. Now, where can I get the bulbs for the push button switches on the front panel?

---

---

Subject: Re: 250 Bass Amp Head

Posted by [stevem](#) on Sat, 06 Mar 2021 16:37:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The bulbs are a number 335 and can be removed and installed from the front of the amp much easier than from the inside of the amp by using needle nose pliers to carefully remove the blue lens from the face of the switch.

Use some clear tubing to remove the old bulb and install the new one.

Do a search on line for the bulbs, I think I saw some on Amazon.

---